



BUILD IT BEAUTIFULLY

GROUND FACE MASONRY

With these units, durability, efficiency and affordable construction have never looked so good. This is masonry elegance at its best.



Building the future™


GROUND FACE UNITS

Ground Face units give architects and designers even more textures and finishes. Each unit is ground smooth to achieve the desired color and finish. And a wide array of available shapes and sizes provides the design flexibility needed to create one-of-a-kind building structures. Meeting or exceeding ASTM-C90 standards, CEMEX Ground Face units provide architectural beauty, quality and durability at a cost to fit any budget.




GROUND FACE MASONRY SHAPES AND SIZES


Sizes and shapes shown represent available units. For custom applications, questions and additional information, please contact your CEMEX representative.




GF STD
Available in:
4", 8", 10", 12"




GF STD Single-Scored
Available in:
4", 8", 10", 12"




GF Return Corner
Available in:
4", 8", 10", 12"




GF "L" Return Corner
Available in:
4"




GF Beveled Transition
Available in:
4", 8"



GF Bond Beam
Available in:
8", 10", 12"



**GF Bond Beam
Single-Scored**
Available in:
8", 10", 12"



GF Half-High
Available in:
4", 8", 10", 12"



GROUND FACE COLORS

Due to the nature of print reproduction, colors may not appear completely accurate. Final selection should be made from actual samples. Please contact your local CEMEX representative or call 888-279-1654 for samples. Custom colors are available at no additional costs.



Charcola



Salt & Pepper



Pink Cream



Mesquite



Watermelon



Sea-View



Buff




Buckskin



Natural Gray




Brownstone




Saffron



White



Suntan Yellow



Redstone



Sand Dune



Black Pearl

NOTE: Please contact your CEMEX representative for all available colors, shapes and sizes



SPECIFICATIONS

GROUND FACE MASONRY

EXPOSED GROUND FACE UNITS

All exposed units indicated on the drawings as Ground Face Concrete Masonry Units shall be manufactured by CEMEX. The color shall be _____, as required by the designing architect.

All units submitted shall be regular weight with custom color as specified and shall meet all requirements of ASTM C-90-latest revision. All ground face units shall be ground smooth to achieve the required product finish.

The manufacturer shall be a quality ground face block producer for a minimum of five (5) years or more.

Note: The designing architect shall specify how the Ground Face units are to be laid and indicate how mortar joints are to be tooled.

All return corners, bond beams and special units shall be part of this section.

All units are to be manufactured with the integral water-repellent admixture DRY-BLOCK® as manufactured by Grace Construction Products.

All Ground Face units shall be shipped on wooden pallets. The purchasing contractor assumes daily responsibility for keeping units covered with 4-mil poly or poly bags.

During construction, it is most important that in-place units be kept as clean as possible and protected from mortar splatters and smears.

Cleaning should be done with a detergent masonry cleaner. Use no acid solutions on Ground Face units. Clean a sample test area before proceeding with final applications of any cleaning solution.



Building the future™

4040 SAND MINE ROAD

DAVENPORT, FL 33897

888-297-1654

WWW.CEMEXUSA.COM