



BUILD IT BEAUTIFULLY

ARCHITECTURAL MASONRY SOLUTIONS SPLIT FACE AND RIBBED UNITS


Design and creativity have no bounds when multiple surface textures are combined with CEMEX's wide selection of sizes, shapes and colors of architectural concrete masonry.




Building the future™

ARCHITECTURAL MASONRY SHAPES & SIZES


Sizes and shapes shown represent available units. For custom applications, questions and additional information, please contact your CEMEX representative.




4" Split Face Half-High




4" Smooth Half-High




**4" Smooth Scored
Half-High**




8" Split Face Half-High




**8" Split Face
Half-High Return**




**8" Smooth Scored
Half-High**




12" Split Face Half-High




12" Smooth Half-High



**12" Smooth Scored
Half-High**



**4" Split & Smooth Face
1" Chamfer**




**8" Split Face Open
Bottom Bond Beam**


**8" Split & Smooth Face
2" Chamfer**

ARCHITECTURAL SPLIT FACE


Sizes and shapes shown represent available units. For custom applications, questions and additional information, please contact your CEMEX representative.




4" Split Face Regular




4" Split Face Half




4" Split Face w/ 8" Return Corner




8" Split Face Regular




8" Split Face Ret. Corner




8" Split Face Regular Bond Beam




8" Split Face Solid Bond Beam




10" Split Face Regular




10" Split Face Corner




10" Split Face Regular Bond Beam



12" Split Face Regular



12" Split Face Regular Bond Beam




12" Split Face Solid Bond Beam


NOTE: Please contact your CEMEX representative for all available colors, shapes and sizes.

ARCHITECTURAL SPLIT SCORED


Sizes and shapes shown represent available units. For custom applications, questions and additional information, please contact your CEMEX representative.




4" Split Score Regular




4" Split Score w/ 8" Return Corner




8" Split Score Regular




8" Split Score Ret. Corner



8" Split Score Bond Beam




12" Split Score Regular




12" Split Score Bond Beam


ARCHITECTURAL SPLIT RIB




4" 8-Split Rib




4" 8-Split Rib Ret. Corner



8" 8-Split Rib



8" 8-Split Rib Ret. Corner




8" 8-Split Rib Bond Beam

SPLIT FACE FACE COLORS

Due to the nature of print reproduction, colors may not appear completely accurate. Final selection should be made from actual samples. Please contact your local CEMEX representative or call 888-279-1654 for samples. Custom colors are available at no additional costs.



Light Plum



Camel



Pink Cream



Brownstone



Nutmeg




Winter White



Buff




Walnut



Terra-Cotta



Black Charcoal



Saffron



Putty



Sandpebble



Brick



Chestnut



Brown

NOTE: Please contact your CEMEX representative for all available colors, shapes and sizes



SPECIFICATIONS

SPECIFICATION ARCHITECTURAL SPLIT-FACE UNITS

Exposed architectural split-face masonry units shall be manufactured in accordance with ASTM C-90 latest revisions.

Pattern of block shall be _____, color to be _____, as selected from manufacturer's developed colors.

Architectural units are to be manufactured by CEMEX.

Other manufacturers of equal quality are to be submitted and approved by the architect ten (10) days prior to bid date.

All manufacturers of colored masonry are to certify of being a quality colored block producer for a minimum period of ten (10) years or more.

Units having a split-face or split-rib shall be manufactured with a chamfered edge on each side of the split area vertically to insure a controlled straight break on the face shell of the unit.

All architectural units are to be laid as indicated by the architect with the mortar joints tooled per the architect's preference.

Job Site Protection: Ship masonry units on wooden pallets. Upon delivery to the job site, architectural units are to be covered with 4-mil plastic bags. It is then the responsibility of the purchasing contractor to keep block dry and covered.

Wall Protection: In instances where two (2) or more different colored units are being laid in the same wall, protect the lower colored units from splatters above. Smooth colored units are of most importance for the protection due to damaging the surface of the unit. Remove splatters and smears prior to mortar full set.

All exterior masonry units shall contain the recommended amount of integral water repellent DRY-BLOCK® as manufactured by Grace Construction Products.

Only liquid polymer water repellent material accepted. Manufacturer of masonry units shall certify that units meet water repellent manufacturer's prequalification test for performance.



Building the future™

4040 SAND MINE ROAD

DAVENPORT, FL 33897

888-297-1654

WWW.CEMEXUSA.COM